

MR Series

Sunlite LED MR16 Colored Mini Reflector 2.8W (20W Halogen Equivalent) Light Bulb (GU10) Base, Green

Colored Series

DESCRIPTION:

Sunlite LED MR16 lamps are extremely energy efficient and will help get your monthly energy costs down to their bare minimum. These lamps can last up to fifteen times longer than their halogen counterparts thereby reducing the hassle of replacements. Sunlite LED lamps do not release any hazardous gasses, so by using these lamps you get to do a little more to protect our environment. You won't lose out on light output or ambiance either; Sunlite LED bulbs deliver a high lumens-per-watt ratio and produce a bright, crisp light in a variety of colors. This Sunlite 120 volt, 2.8 watt, MR16 type LED provides a strong light output using 60 Led's. It features a gu-10 base and can last up to 30,000 hours. It produces a brilliant green light. The Sunlite MR16/60LED/2.8W/GU10/120V/G LED lamp lasts long, reduces energy costs and can fit right into your home application or into the most cutting-edge, state of the art lighting design project.

FEATURES:

- 2.8 Watt; 120 Volt
- Green Color
- GU10 Base; 60 Led's
- 30,000 hours average lamp life
- MR16/60LED/2.8W/GU10/120V/G



SPECIFICATIONS:

General Characteristics

Bulb Shape	MR16
Nanometer	520
Average Rated Hours	30000
Base	Twist & Lock (GU10)
Average Life Span Years	27
Dimmable	No

Electrical Characteristics

Watts	2.8
Volts	120
Equivalent Wattage	20
LED Chip Manufacturer	Epistar

Light Characteristics

Color Rendering Index CRI	75
Emitted Color	Green

Additional Features

Mercury Free	Yes
---------------------	-----

Product Dimensions

MOL (in)	2.2
Diameter (in)	1.96
Item Dimension (in)	(W) 1.97 (H) 2.13 (D) 1.97
Package Dimension (in)	(W) 2.1 (H) 2.2 (D) 2.8
Package Weight (lb)	0.050

Product Data

Case Unit Rate	12
Pack Size	1
Item UPC	653703803272
Package Type	Box



VARIATIONS:



Item Number	Description	Watts	Eq Watts	CRI	Color	Hours	Pack
80327-SU	MR16/60LED/2.8W/GU10/120V/G	2.8	20	75	GREEN	30000	1
80328-SU	MR16/60LED/2.8W/GU10/120V/R	2.8	20	75	RED	30000	1