

Sunlite 88180 LED Portable Work Light Fixture, 25' Power Cord, 12 Watts, 6200K Daylight, 1200 Lumens, Built-In Outlet, ETL Listed, Yellow, For Construction, Work Sites & Garage Use

DESCRIPTION:

The LED Portable Work Light Fixture from Sunlite is a lightweight handheld work light which is ideal for use wherever extra light is needed. For vehicle repair, work benches, garages, attics, basements, and more. Made from commercial grade materials for commercial use as well as residential. This 6200K daylight-LED light produces a consistent, natural and energy-efficient light. With integrated LEDs and a long 50,000-hour life cycle, this lamp will offer years of dependable, maintenance-free service and provide 1200 lumens of light while only using 12 watts of electricity. This fixture has a 25 foot durable & waterproof 16wg cord. Convenient grounded 120 volt outlet on the base for plugging in other tools up to 12 amps. The built-in magnet on the back of the light for attaching to metal surfaces. Sturdy folding hook built-in for another hanging option. This fixture is ETL Listed for use in dry locations and has passed safety tests. Dimensions: 13.54" H x 3.22" D.

FEATURES:

- **EASY-TO-USE DESIGN** – This lightweight handheld work light is ideal for use wherever extra light is needed. For vehicle repair, work benches, garages, attics, basements, and more. Made from commercial grade materials this droplight is perfect for commercial use as well as residential.
- **BRIGHT DAYLIGHT** - This 6200K daylight-LED light produces a consistent, natural and energy-efficient light. With integrated LEDs and a long 50,000-hour life cycle, this lamp will offer years of dependable, maintenance-free service and provide 1200 lumens of light while only using 12 watts of electricity.
- **HEAVY DUTY CORD** - This fixture has a 25 foot durable & waterproof 16wg cord. Convenient grounded 120 volt outlet on the base for plugging in other tools up to 12 amps.
- **POWERFUL MAGNET** - The built-in magnet on the back of the light for attaching to metal surfaces. Sturdy folding hook built-in for another hanging option.
- **ETL LISTED** - This fixture is ETL Listed for use in dry locations and has passed safety tests. Dimensions: 13.54"



SPECIFICATIONS:

General Characteristics

| | |
|--------------------------------|---------------|
| Average Rated Hours | 50000 |
| Finish | Sand Blast |
| Average Life Span Years | 46 |
| Dimmable | No |
| Material | Plastic |
| Lens Material | Polycarbonate |

Electrical Characteristics

| | |
|------------------------------|--------------|
| Watts | 12W |
| Volts | 120V |
| LED Chip Manufacturer | COB |
| Temperature | -4°F - 104°F |

Light Characteristics

| | |
|----------------------------------|----------|
| Lumens Brightness | 1200 |
| Color Rendering Index CRI | 62 |
| Emitted Color | Daylight |
| Color Temperature Kelvin | 6200K |
| Beam Angle | 120° |

Fixture Characteristics

| | |
|---------------------------|----------|
| Mounting | Portable |
| Fixture Technology | LED |
| Use Location | Outdoor |

Additional Features

| | |
|---------------------------|---------------------------|
| Safety Rating Mark | ETL Listed - Dry Location |
|---------------------------|---------------------------|

Product Dimensions

| | |
|-------------------------------|-----------------------------|
| Item Dimension (in) | (W) 4.72 (H) 17.32 (D) 3.94 |
| Package Dimension (in) | (W) 4.75 (H) 16.5 (D) 4 |
| Package Weight (lb) | 3.08 |

Product Data

| | |
|-----------------------|--------------|
| Case Unit Rate | 6 |
| Item UPC | 653703881805 |
| Warranty Years | 1 |

