

ED Series

**Sunlite 03653-SU MP100/C/U/MED
M102/O Protected Metal Halide Lamp, 150
Watts, Medium Base (E26), Pulse Start,
ED17, 15,000 Hours Life, 12600 Lumen,
Coated White Finish, 4200K**

Protected Metal Halide

DESCRIPTION:

Sunlite high intensity discharge lamps are perfect for outdoor lighting and commercial interiors. Energy efficient HID lamps offer exceptional efficacy, great color rendition, have a long service life and excellent lumen maintenance. These 150 watt protected pulse start metal halide bulbs have a bright 12600 lumen output. They are medium base (E26), ED17 bulbs with an average life span of 15,000 hours. Use in street lights, parking lot fixtures, perimeter lighting, wall packs, and other commercial and industrial lighting applications. ANSI Code M102/O. Confirm ANSI Code to help determine the correct bulb for your fixture and the ballast it uses. Bulb measurements are 2.121 inches in diameter, 5.412 inches tall.

FEATURES:

- **PROTECTED METAL HALIDE** - Sunlite high intensity discharge lamps are perfect for outdoor lighting and commercial interiors. These energy efficient HID lamps offer exceptional efficacy, great color rendition, have a long service life and excellent lumen maintenance.
- **HIGH INTENSITY DISCHARGE** - This 150 watt bulb puts out a bright 12600 lumens of light. Color temperature is 4200K. Coated White glass bulb.
- **MEDIUM BASE** - Larger medium base (E26) for use in street lights, parking lot fixtures, perimeter lighting, and other commercial and industrial lighting applications. Bulb measurements 2.121 inches diameter, 5.412 inches tall.
- **PULSE START** - These protected pulse start bulbs feature a long 15,000 hour average lifespan.
- **ANSI CODE M102/O** - This metal halide bulb is for use in M102/O ballast fixtures. Confirm ANSI Code to help determine the correct bulb for your fixture and the ballast it uses.



SPECIFICATIONS:

General Characteristics

Bulb Shape	ED17
Ansi code	M102/O
Average Rated Hours	15000
Finish	Coated
Base	Medium Screw (E26)
Average Life Span Years	14

Electrical Characteristics

Watts	150
Volts	120

Light Characteristics

Lumens Brightness	12600
Color Rendering Index CRI	65
Emitted Color	Cool White
Color Temperature Kelvin	4200K

Product Dimensions

MOL (in)	5.412
Diameter (in)	2.121"
Item Dimension (in)	(W) 2.12 (H) 5.41 (D) 2.12
Package Dimension (in)	(W) 2.4 (H) 5.8 (D) 2.4
Package Weight (lb)	0.250

Product Data

Case Unit Rate	12
Pack Size	1
Item UPC	653703036533
Warranty Years	1

VARIATIONS:



03653-SU

<i>Item Number</i>	<i>Description</i>	<i>Watts</i>	<i>Lumens</i>	<i>CRI</i>	<i>Kelvin Color</i>	<i>Hours</i>	<i>Pack</i>
03653-SU	MP150/C/U/MED	150	12600	65	4200K CW	15000	1