

Sunlite 89780 LED Commercial UFO High Bay Light Fixture, 100 Watts (250W=), 14000 Lumens, 5000K Super White, Dimmable, UL Listed, Black, 120-277V, IP65, For Warehouses, Factories & Workshops
UFO

DESCRIPTION:

Upgrade to energy-efficient lighting with Sunlite's sleek, UFO-style high bay fixture, featuring a durable, lightweight die-cast aluminum body for optimal heat dissipation. Enjoy 14,000 lumens of 5000K Super White light while consuming only 100 watts, resulting in significant energy savings. With a 50,000-hour lifespan, 300 built-in LEDs, and 0-10V dimmability, experience reliable, maintenance-free lighting in commercial spaces such as warehouses, workshops, and retail areas. UL Listed for wet locations and IP65 rated, this fixture is suitable for 120-277-volt electrical systems and includes a 39.6" AC cord. Dimensions: 10.8" D x 4.6" H.

FEATURES:

- **UPGRADE TO LED** - Replace older high bay lights with energy-efficient LEDs. These UFO-style fixtures feature a durable and lightweight die-cast aluminum body designed for pendant mounting that provides optimal heat dissipation. Great for new installations, too.
- **SUPER WHITE LIGHT** - Color temperature is 5000K Super White with a bright 14000-lumen output while only using 100 watts of electricity. Each fixture has 300 built-in LEDs.
- **LONG LIFE SPAN** - A long, 50,000-hour lifespan means years of reliable and maintenance-free service with no bulbs to replace. Benefit from significant energy savings over time.
- **DIMMABLE LED** - The fixture can be dimmed (0-10V Dimmable) when installed with an LED-compatible dimmer.
- **UL LISTED** - UL Listed for wet location installation. High lumen output is designed in warehouses, commercial garages, workshops, factories, retail spaces, or any commercial environment. IP65 Rated. For use on 120-277-volt electrical systems. Includes 39.6" AC cord. Fixture Dimensions: 10.8" D x 4.6" H.



SPECIFICATIONS:

General Characteristics

Average Rated Hours	50000
Finish	Black
Average Life Span Years	46
Dimmable	Yes
Dimming Type	0-10V Low Voltage
Dimming Percentage	10-100%
Material	Aluminum
Lens Material	Polycarbonate
Lens Finish	Clear

Electrical Characteristics

Watts	100
Volts	120-277
LED Chip Manufacturer	SMD2835
Power Factor	0.9
Temperature	-4°F - 122°

Light Characteristics

Lumens Brightness	14000
Color Rendering Index CRI	80
Emitted Color	Super White
Color Temperature Kelvin	5000K
Beam Angle	90°

Fixture Characteristics

Mounting	Pendant
Fixture Technology	LED
Use Location	Indoor

Additional Features

Safety Rating Mark	UL Listed - Wet Location
DLC Classification	Premium
Mercury Free	Yes
CE Certified	Yes

Product Dimensions

MOL (in)	4.6
Diameter (in)	10.8
Item Dimension (in)	(W) 10.8 (H) 4.6 (D) 10.8
Cord Length	40"

Product Data

Item UPC	653703897806
Warranty Years	5

ACCESSORIES:

Catalog # 89699-SU
MS/LFX/HB/V2

Catalog # 89785-SU
RC/LFX/HB

Catalog # 89787-SU
PCR/LFX/HB/V2

Catalog # 89789-SU
PCL/LFX/HB/V2

Catalog # 89790-SU
SC/LFX/HB