

Sunlite 89783 LED Commercial UFO High Bay Light Fixture, 240 Watts, 33600 Lumens, 5000K Super White, Dimmable, UL Listed, Black, 120-277V, IP65, For Warehouses, Factories & Workshops
UFO

DESCRIPTION:

Upgrade to energy-efficient lighting with Sunlite's sleek, UFO-style high bay fixture, featuring a durable, lightweight die-cast aluminum body for optimal heat dissipation. Enjoy 33,600 lumens of 5000K Super White light while consuming only 240 watts, resulting in significant energy savings. With a 50,000-hour lifespan, 330 built-in LEDs, and 0-10V dimmability, experience reliable, maintenance-free lighting in commercial spaces such as warehouses, workshops, and retail areas. UL Listed for wet locations and IP65 rated, this fixture is suitable for 120-277-volt electrical systems and includes a 39.6" AC cord. Dimensions: 12.6" D x 5" H.

FEATURES:

- **UPGRADE TO LED** - Replace older high bay lights with energy-efficient LEDs. These UFO-style fixtures feature a durable and lightweight die-cast aluminum body designed for pendant mounting that provides optimal heat dissipation. Great for new installations, too.
- **SUPER WHITE LIGHT** - Color temperature is 5000K Super White with a bright 33600-lumen output while only using 240 watts of electricity. Each fixture has 330 built-in LEDs.
- **LONG LIFE SPAN** - A long, 50,000-hour lifespan means years of reliable and maintenance-free service with no bulbs to replace. Benefit from significant energy savings over time.
- **DIMMABLE LED** - The fixture can be dimmed (0-10V Dimmable) when installed with an LED-compatible dimmer.
- **UL LISTED** - UL Listed for wet location installation. High lumen output is designed in warehouses, commercial garages, workshops, factories, retail spaces, or any commercial environment. IP65 Rated. For use on 120-277-volt electrical systems. Includes 39.6" AC cord. Fixture Dimensions: 12.6 D x 5" H.



SPECIFICATIONS:

General Characteristics

Average Rated Hours	50000
Finish	Black
Average Life Span Years	46
Dimmable	Yes
Dimming Type	0-10V Low Voltage
Dimming Percentage	10-100%
Material	Aluminum
Lens Material	Polycarbonate
Lens Finish	Clear

Electrical Characteristics

Watts	240
Volts	120-277
LED Chip Manufacturer	SMD2835
Power Factor	0.9
Temperature	-4°F - 122°

Light Characteristics

Lumens Brightness	33600
Color Rendering Index CRI	80
Emitted Color	Super White
Color Temperature Kelvin	5000K
Beam Angle	90°

Fixture Characteristics

Mounting	Pendant
Fixture Technology	LED
Use Location	Indoor

Additional Features

Safety Rating Mark	UL Listed - Wet Location
DLC Classification	Premium
Mercury Free	Yes
CE Certified	Yes

Product Dimensions

Diameter (in)	12.5
Item Dimension (in)	(W) 12.6 (H) 5 (D) 12.6
Cord Length	39.5"

Product Data

Item UPC	653703897837
Warranty Years	5

ACCESSORIES:

Catalog # 89699-SU
MS/LFX/HB/V2

Catalog # 89785-SU
RC/LFX/HB

Catalog # 89787-SU
PCR/LFX/HB/V2

Catalog # 89788-SU-DEACT
AR/LFX/HB

Catalog # 89789-SU
PCL/LFX/HB/V2

Catalog # 89790-SU
SC/LFX/HB