

LED TROFFERS

2x2' & 2x4'

- For recessed commercial applications such as offices, hospitals, schools etc. Suitable for use in standard 15/16" inverted T-Bar grid ceilings.



- High performance optical engine delivers main beam focus through the integrated acrylic lens.
- Lumieo® acrylic diffuser manages the balance of efficiency and aesthetics.
- Linear arrayed LED modules provide diffused, but effective illumination.
- LED light engine (optional) by LG Innotek, global leader in LED technology.
- UL listed and DLC approved.

LED light source and luminaire specifications

ELL LED Troffer		
Specification	2'x2'	2'x4'
Input Wattage	35.6	52
Delivered Lumens (lms)	3548	5827
Efficacy (LpW)	99.7	111.9
Color Rendering Index (CRI)	84.3	84.4
Color Temperature (CCT) k	3500, 4000	3500, 4000
Minimum Ambient Temp (°F)	-4	-4
Maximum Ambient Temp (°F)	158	158
Dimming	0-10v	0-10v
Rated Life (L70)	50000	50000
Warranty	5 years	5 years
Voltage (V)	120-277v	120-277v
Operating Frequency (Hz)	50/60	50/60
UL	Yes	Yes
FCC	Compliant	Compliant

Catalog # 90355 LFX-RL-2x2-37W-LED-MV-35K

Catalog # 90356 LFX-RL-2x2-37W-LED-MV-40K

Catalog # 90357 LFX-RL-2x4-55W-LED-MV-35K

Catalog # 90358 LFX-RL-2x4-55W-LED-MV-40K

