

**Sunlite 85215 2x4 FT LED Flat Panel Troffer Light Fixture, 34 Watts, 4285 Lumens, 35K/40K/50K Adjustable Color Temperature, 120-277V, Dimmable, 50,000 Hour Life Span, Energy Star, UL & DLC Approved**

**DESCRIPTION:**

The Sunlite 2x4 Troffer Panel Fixture is an excellent addition to any environment. It features a slim design metal body with white trim and a shatter-resistant frosted lens. Output is a bright 4285 lumens while only using 34 watts of electricity. High color rendering at 80 CRI. This dimmable fixture has a 50,000-hour life span and is ETL Listed for damp location installation. Installing these Energy Star Certified fixtures may qualify you for state or local energy rebates. Fixture Measurements: H-0.36" W: 24" D: 48"



**FEATURES:**

- **DURABILITY-** The Sunlite Flat Panel Troffer Fixture is an excellent addition to any atmosphere. It features a slim, robust aluminum alloy frame and a shatter-resistant frosted lens. LED panel lights are the ideal method in replacing traditional incandescent lamps. Also, their service life is five times that of the standard fluorescent panels.
- **ADJUSTABLE COLOR TEMPERATURE:** Test different color temperatures before installation and never be dissatisfied with CCT again. This simplistic fixture has adjustable LED color-changing technology (3500K, 4000K, 5000K), quickly meeting different demands in areas. With a simple switch inside the fixture, the color temperature could be changed. PLEASE NOTE: select the desired color temperature before completely mounting the fixture. (Instructions included).
- **DIMMABLE -** Fixture can be dimmed when installed with an LED-compatible dimmer. Output is a bright 4285 lumens (100w equivalent) while only using 34 watts of electricity. Operates within 120-277V AC, 10%-100% dimming range, and has a high color rendering at 80 CRI. The long 50,000-hour life span is significant in energy savings over time.
- **ENERGY STAR & UL LISTED -** This fixture is Energy Star Certified. The energy-saving panel blends effective LEDs with high-efficiency light smoothing optics to provide excellent light quality and energy-saving effects, low heat generation, high efficiency, and 50% energy saving than your traditional fluorescent tube lighting. These fixtures are perfect for commercial, industrial, and residential applications such as offices, hospitals, schools, retail, and workshops. UL Listed for damp location installation. Each fixture includes installation hardware and instructions. Fixture Measurements: H-0.36" W: 24" D: 48"
- **EASY INSTALLATION-** The LED panel is easily installed and has convenient recessed mounting for standard grid ceilings. For drop-in installation, this LED panel ceiling light has a simple installation method. Just insert it into the open grid space and connect it to the junction box. Refer to installation instructions for detailed steps.

## SPECIFICATIONS:

### General Characteristics

Average Rated Hours	50000
Finish	White
Average Life Span Years	46
Dimmable	Yes
Dimming Type	0-10V Low Voltage
Dimming Percentage	10-100%
Material	Steel & PC
Lens Finish	White

### Electrical Characteristics

Watts	25/30/34
Volts	120-277
LED Chip Manufacturer	Seoul 3528
Power Factor	0.99
Temperature	-20-50°

### Light Characteristics

Lumens Brightness	3350/3900/4285
Color Rendering Index CRI	80
Emitted Color	CCT Selectable
Color Temperature Kelvin	35K/40K/50K
Beam Angle	110°

### Fixture Characteristics

Shape	Rectangle
Number of Lights	1
Mounting	Recessed
IC Rating	Yes
Fixture Technology	LED
Use Location	Indoor

### Additional Features

Safety Rating Mark	UL Listed - Damp Location
Safety Rated For Canada	Yes
Safety Rated For USA	Yes
DLC	Yes
DLC Number	PLNUX3GQDS4L
DLC Classification	Standard

### Product Dimensions

Size	2X4
Item Dimension (in)	(W) 48 (H) 2.75 (D) 24
Package Dimension (in)	(W) 24.68 (H) 3.15 (D) 49.5
Package Weight (lb)	16.46

### Product Data

Pack Size	1
Item UPC	10653703852154
Warranty Years	5

---

**ACCESSORIES:**

Catalog # 90497-SU  
LFX/2X4/MW/SCT/BLS

Catalog # 90496-SU  
LFX/2X4/MW/SCT/EM/BLS

Catalog # 90498-SU  
LFX/2X4/MW/SCT/EM

Catalog # 90494-SU  
LFX/2X4/MW/SCT/EM/MS

Catalog # 90495-SU  
LFX/2X4/MW/SCT/MS

Catalog # 89159-SU  
EMERGENCY

Catalog # 85124-SU  
LFX/TROFFER