

ST Series

Sunlite T5/LED/2'/11W/IS/40K LED 11W 2 Foot Instant Start T5 Tube Light Fixtures, 4000K Cool White Light, Medium Bi-Pin (G13) Base

Plug and Play

DESCRIPTION:

Sunlite's 2 pin tubular LED lamps are the best replacement lamps to your traditional fluorescent tube lamps for a wide range of settings, including schools, hospitals and other professional settings. Containing no mercury content whatsoever, these lamps promote a much healthier environment when compared to any competing fluorescent lamp. WarningBefore installing, be sure to confirm this T8 Plug & Description of the sure to confirm the security List can found on www.sunlite.com under the specific Item Number. Make sure the lighting fixture is wired correctly per the ballast or lamp instructions. Never install or remove the T8 lamp with the lighting fixture energized, or arcing at the pins may occur. Sunshine Lighting assumes no liability for incidental or consequential damages resulting from the misuse of this product.



- Produces An Efficient 4000K Cool White Beam Of Light For All Your Ceiling Fixtures And More
- On Average, These 120-277 Multi-Volt LED Lamps Last An Astonishing 50000 Hours And Are Fitted With A Medium Bi-Pin (G13) Base
- High Quality Construction Plug And Play Tube Lamp That Consumes Only 11 Watts Of Energy; Replaces Tubular Linear Fluorescent Lamps
- Two Foot Energy Efficient LED T5 Ceiling Light Fixture Lamps Perfect For Your Bathroom, Hallway, And/Or Office Space
- High-Quality, UL Classified, Modern Replacement LED Light Bulbs Sold At A Highly Competitive Price





SPECIFICATIONS:

General Characteristics

Bulb Shape Average Rated Hours Finish Base

Average Life Span Years Dimmable

Material

Electrical Characteristics

Watts
Equivalent Wattage
Power Factor
Temperature
Ballast Factor

Ballast Factor

Light Characteristics

Lumens Brightness

Color Rendering Index CRI Emitted Color Color Temperature Kelvin

Additional Features

Safety Rating Mark
UL Rated Enclosed Fixtures
Safety Rated For Canada
Safety Rated For USA

T5 50000 White Miniature Bi-Pin (G5) 46

No Glass

11 F24T5/HO 0.9 -20° to 45°

High Output (HO) Required

UL Classified - Damp Location

Yes Yes Yes

1400

4000K

Cool White

82

Product Dimensions

Size
MOL (in)
Diameter (in)
Item Dimension (in)
Item Weight (lb)
Package Dimension (in)
Package Weight (lb)

Product Data

Case Unit Rate
Pack Size
Item UPC
Warranty Years
Package Type

2 Foot 23.22

(W) 0.6 (H) 0.6 (D) 10.1

0.020

0.64

(W) 0.7 (H) 0.7 (D) 10.2

0.030

10

653703882215

5 Sleeve