

#### Catalog # 88269-SU PLD/LED/9W/IS/35K/V2

#### Plug-In

Sunlite 88269-SU LED PLD Light Bulb, 9 Watts (26W Equivalent), 950 Lumens, G24q Base, Ballast Dependant, CFL Replacement, UL Listed, 35K - Neutral White 1 Pack

Plug and Play

#### **DESCRIPTION:**

Replace your 26 watt compact fluorescent PL bulbs with energy efficient 9 watt LED bulbs from Sunlite. These 4-Pin base (G24q) bulbs are plug and play with no ballast bypass required. 270 degree beam angle that can be rotated at the base for optimal coverage. LED Technology means flicker free light that comes on instantly with no warm-up time and no buzzing like CFL bulbs. Output is a bright 950 lumen with 3500K color temperature at 3500K. Provides up to 50,000 hours of energy efficient light means you'll have to replace difficult to access bulbs less often. Unlike CFL bulbs these LED lamps contain no hazardous chemicals. They are UL Listed for damp location installation and DLC Listed for quality and efficiency.

#### FEATURES:

- UPGRADE TO LED Replace your 26 watt compact fluorescent PL bulbs with energy efficient 9 watt LED bulbs from Sunlite. These 4-Pin base (G24q) bulbs are plug and play with no ballast bypass required. 270 degree beam angle that can be rotated at the base for optimal coverage.
- NO FLICKERING OR BUZZING LED Technology means flicker free light that comes on instantly with no warm-up time and no buzzing like CFL bulbs. Output is a bright 950 lumen with Neutral White color temperature at 3500K.
- ENERGY EFFICIENT These 9 watt LED bulbs are direct replacements for 26 watt CFL bulb. That's a 65% energy savings. Low annual operating costs of only \$1.08. (Based on 3 Hours/Day at \$0.11/kWh)
- LONG LIFE SPAN Provides up to 50,000 hours of energy efficient light means you'll have to replace difficult to access bulbs less often. Makes commercial and residential fixtures virtually maintenance-free.
- A SAFER CHOICE Unlike CFL bulbs these LED lamps contain no hazardous chemicals. They work with your existing ballasts so no special wiring or modifications are needed. They are UL Listed for damp location installation and DLC Listed for quality and efficiency.



# sunlite

## **SPECIFICATIONS:**

#### **General Characteristics**

### **Product Dimensions**

Bulb Shape	PLD	MOL (in)	6.57
Average Rated Hours	50000	Item Dimension (in)	(W) 1.4 (H) 6.61 (D) 1.4
Finish	White	ltem Weight (lb)	0.170
Base	4-Pin (G24q)	Package Dimension (in)	(W) 1.42 (H) 3.16 (D) 1.44
Average Life Span Years	46	Package Weight (lb)	0.210
Dimmable	No		
Material	Aluminum & Plastic	Product Data	
		Case Unit Rate	12
Electrical Characteristics		Pack Size	1

#### E

Watts	9	Item UPC
Equivalent Wattage	18	Warranty Years
Temperature	-20-45?	Package Type

#### **Light Characteristics**

Lumens Brightness	1050
Color Rendering Index CRI	82
Emitted Color	Neutral White
Color Temperature Kelvin	3500K
Beam Angle	270°

#### **Additional Features**

Safety Rating Mark	UL Listed - Damp Location	
UL Rated Enclosed Fixtures	Yes	
DLC	Yes	
DLC Number	PL2BX9HCZT3P	
DLC Classification	Standard	

653703882697 5

Box

Catalog # 88269-SL	J
PLD/LED/9W/IS/35K/	/2