

LED T5 Shatterproof Glass Tube Color Selectable


sunlite



Double Sided G5 Bi-Pin
Frosted Lens
Shatterproof Glass PET Coating
Available 2FT, 3FT, & 4FT




Plug and Play Installation



LED tube lamp has the live and neutral pins on the opposite sides of the lamp. Use shunted lamp holders.

Item#	Description	Watt	Replacement	Lumen	LPW	CRI	Volt	Lens	Kelvin	Hours	Mol (in)
Plug and Play Installation											
88009-SU	T5/LED/IS/2'/12W/4SCT	12	F14T5/F24T5	1600	133	83	120-277	Frosted	35K/40K/50K/65K	50000	24
88011-SU	T5/LED/IS/3'/18W/4SCT	18	F21T5/F39T5	2500	139	83	120-277	Frosted	35K/40K/50K/65K	50000	36
88013-SU	T5/LED/IS/4'/24W/4SCT	24	F28T5/F54T5	3500	146	83	120-277	Frosted	35K/40K/50K/65K	50000	48

Advanced Bypass Installation



LED tube lamp has live and neutral pins on the opposite side. When you wire a dual-ended tube, you will need to connect neutral wires to one end and live wires to the other end. Using shunted lamp holders connect live to one end, and neutral to other end as shown.

Item#	Description	Watt	Replacement	Lumen	LPW	CRI	Volt	Lens	Kelvin	Hours	Mol (in)
Advanced Bypass Installation											
88010-SU	T5/LED/BPD/2'/12W/4SCT	12	F14T5/F24T5	1800	120	83	120-277	Frosted	35K/40K/50K/65K	50000	24
88012-SU	T5/LED/BPD/3'/18W/4SCT	18	F21T5/F39T5	2600	144	83	120-277	Frosted	35K/40K/50K/65K	50000	36
88014-SU	T5/LED/BPD/4'/24W/4SCT	24	F28T5/F54T5	3200	133	83	120-277	Frosted	35K/40K/50K/65K	50000	48