

LED Plug-In Lamps Color Selectable


sunlite

Installation
Type A+B
Plug & Turn On



88811-SU

uses **9.5w**
26w
replacement




G24q 4-PIN BASE



88806-SU

uses **6w**
13w
replacement




GX23 2-PIN BASE

Rotatable
180 Degree



88810-SU

uses **9.5w**
26w
replacement




G24q 4-PIN BASE

Rotatable
180 Degree



88808-SU

uses **9.5w**
26w
replacement



G24d 2-PIN BASE

Fewer SKUs, Save Stocking Spaces !

Eliminates the need to stock separate bulbs for each color temperature.



Item#	Description	Watt	Eq. W	Lumen	LPW	CRI	Lens	Kelvin	Volt	Hours	Mol (in)	Features	CTN
G24q 4-Pin Base Type A+B													
88811-SU	PLV/LED/HY/4P/9.5W/3SCT	9.5	26	1050	111	80	White	30K/40K/50K	120-277V	50000	5.0	DL	12
GX23 2-Pin Base													
88806-SU	PLD/LED/HY/6W/3SCT	6	13	650	108	80	White	30K/40K/50K	120-277V	50000	7.48	DL	12
G24q 4-Pin Base Rotatable													
88810-SU	PLD/LED/HY/4P/9.5W/3SCT	9.5	26	1050	111	80	White	30K/40K/50K	120-277V	50000	6.75	DL	12
G24d 2-Pin Base Rotatable													
88808-SU	PLD/LED/HY/2P/9.5W/3SCT	9.5	26	1050	111	80	White	30K/40K/50K	120-277V	50000	6.75	DL	12

DL = Rated Damp Location